




Information and Communication Technology:

The INFORMATION THEORY (CONTINUED)



The INFORMATION THEORY



presented by: **Rhiza S. Sadjad**

rhiza@unhas.ac.id <http://www.unhas.ac.id/rhiza/>

The INFORMATION CAPACITY or Bit Rate of Data Transmission



1 bit per second → 1 bps

**8 to 10 bit per second → 1 Byte per second
1 Bps**

1000 bit per second → 1 Kbps

1000 Kbps → 1 Mbps


1000 Mbps → 1 Gbps

The Information Capacity (Bit Rate)



According to Shannon [1948], there are 2 (two) factors related to the information capacity:

- ***Bandwidth***
- ***Channel Quality (Signal to Noise Ratio, S/N atau SNR)***



The Information Theory


The Communication Model

[1948] Claude E. Shannon, "***A Mathematical Theory of Communication***" (a technical notes)



[***/home/rhiza/Desktop/shannon.pdf***](#)

[1949] Claude E. Shannon and Warren Weaver, "***The Mathematical Theory of Communication***" (popular version)

 **The Information Theory**

Communication Model

Shannon and Weaver [1949], simplex mode

INFORMATION

SOURCE

TRANSMITTER

RECEIVED

RECEIVER

DESTINATION





Fig. 1 — Schematic diagram of a general communication system



The Information Theory

The Information Capacity (Bit Rate)

Shannon and Weaver [1949], simplex mode

INFORMATION

SOURCE

TRANSMITTER

RECEIVED

RECEIVER

DESTINATION




Fig. 1 — Schematic diagram of a general communication system.

The Shannon [1948] formula to compute the Information Capacity:

$$\text{Information Capacity [bps]} = (\text{Bandwidth} [\text{Hertz}]) \cdot \log_2 (1 + S/N)$$

Schweber, [1996], page 16

The Information Capacity (Bit Rate)

The Shannon [1948] formula to compute the Information Capacity:

$$\text{Information Capacity [bps]} = (\text{Bandwidth} [\text{Hertz}]) * 2 \log (1 + \text{S/N})$$

Schweber, [1996], page 16

$$\text{Bit Rate} = \text{BW} * 2 \log (1 + \text{S/N})$$

- Bit Rate (The Information Capacity) : The amount of information transmitted in a unit of time [**bit per second, bps**] through a communication channel
- BW (Bandwidth) : The spectrum of signals transmittable in the channel [**Hertz, getaran per detik, cycles per second, cps**], the difference between the highest frequency and the lowest frequency
- S/N (Signal to Noise ratio) : the quality of the channel in terms of the ratio of the transmitted signal power and the noise power



SELESAL

The END

Next:

THE END

The Communication
Mode

